

S SERIES | MODELS S50 / S70

ALL-IN-ONE BENCHTOP MARKING DEVICE



Software:

Programmable from the on-board touch-screen panel and from the new "stamper 2.0" PC software.

Features:

Maximum flexibility of use: different working modes for high definition, high-speed or high depth markings.

Works on all types of metals including hard metals as well as plastic and wood.

Suitable for marking flat and curved surfaces, even without rotation of the part

Marking:

Marking of variable texts, serial numbers, date and time, logos and drawings (DXF and PLT).

20 Native fonts, Anti-stress fonts and all True-Type fonts available.

The size, style and direction of the text can be programmed.

Marking with DATA MATRIX codes according to NASA specifications.

Connections:

Ethernet - USB - RS-232/485 serial - Digital I/O opto-isolated 24VDC.

Memory:

Internal memory: 4GB Micro-SD.

Power supply:

Pneumatic 6 bar max. (10N/L min.) power supply.

90 to 264 VAC (50 / 60Hz) 40W power supply.

Punches available:



S50 3 mm (12 mm bore)

- Standard **KIT-3HS-90-05**
- 60° angle **KIT-3HS-60-03**
- 120° angle **KIT-3HS-120-05**
- **KIT-3HS-120-01** for Data Matrix
- **KIT-3HS-120-02** for Data Matrix

- **KIT-3SD-120-050** diamond
- **KIT-3SD-120-035** diamond for Data Matrix
- **KIT-3HS-60-PL** for plastic
- **KIT-3HS-60-LE** for wood



S50 6 mm (25 mm bore)

- Standard **KIT-6HS-90-05**
- 120° angle **KIT-6HS-120-05**
- **KIT-6HD-120-035** diamond
- **KIT-6HD-120-050** diamond



S70 3 mm (12 mm bore)

- Standard **KIT-3HE-90-05**
- 60° angle **KIT-3HE-60-03**
- 120° angle **KIT-3HE-120-05**
- **KIT-3HE-120-01** for Data Matrix
- **KIT-3HE-120-02** for Data Matrix

- **KIT-3ED-120-050** diamond
- **KIT-3ED-120-035** diamond for Data Matrix
- **KIT-3HE-60-PL** for plastic
- **KIT-3HE-60-LE** for wood

Completely autonomous fixed station with integrated touch screen programming panel

Models available:

S50	electro-pneumatic	marking areas: 130x100 mm
S70	electro-magnetic	marking areas: 130x100 mm

Controller:



Integrated 7" touch screen programming panel

Includes:

Stamper 2.0 PC software
Ethernet, USB, I/O port



Lower side protection shutter

Options:



P-TARG plate for attaching metal plates




BC-DLC bar-code reader for the acquisition of codes to be marked




PDL-INT-01 "start marking" command pedal



COLUMN with custom dimensions



AR1 rotary axis with chuck, maximum capacity 5 Kg diameter 60 mm



AR4 rotary axis with chuck, maximum capacity 80 Kg diameter 200 mm



PRL-70 punch extension cable (+70 mm)